

MACHINE SPECIFICATIONS



© Woodstock International, Inc. • Phone #: (800) 840-8420 • Web: www.woodstockint.com

MODEL W1708 1 HP 12" DISC SANDER

Product Dimensions

Weight..... 68 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 18 x 17-3/8 x 14-1/2 in.
Footprint (Length x Width)..... 13 x 10 in.

Shipping Dimensions

Type..... Cardboard Box
Content..... Machine
Weight..... 74 lbs.
Length x Width x Height..... 18 x 19 x 16 in.

Electrical

Power Requirement..... 110V, Single-Phase, 60 Hz
Prewired Voltage..... 110V
Full-Load Current Rating..... 10A
Minimum Circuit Size..... 15A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 5 ft.
Power Cord Gauge..... 16 AWG
Plug Included..... Yes
Included Plug Type..... 5-15
Switch Type..... Paddle Safety Switch w/Removable Key

Motors

Main

Horsepower..... 1 HP
Phase..... Single-Phase
Amps..... 10A
Speed..... 1725 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer Direct Drive
Bearings..... Sealed & Permanently Lubricated
Centrifugal Switch/Contacts Type..... External

Main Specifications

Disc Sander Info

Disc Diameter..... 12 in.
Disc Speed..... 1725 RPM
Disc Sandpaper Backing Type..... PSA
Table Length..... 17-1/4 in.
Table Width..... 8-1/4 in.
Table Thickness..... 1 in.
Table Tilt..... Left 0, Right 45 deg.

Construction Materials

Base..... Cast Iron
Table..... Cast Iron
Frame..... Steel
Disc..... Cast Aluminum
Miter Gauge..... Plastic/Aluminum
Paint Type/Finish..... Epoxy

Other Related Info

Miter Gauge Slot Width..... 3/4 in.
Miter Gauge Slot Height..... 3/8 in.
Number of Dust Ports..... 1
Dust Port Size..... 2 in.

Other

Country of Origin China
Warranty 2 Years
Approximate Assembly & Setup Time 15 Minutes
ISO 9001 Factory No
Certified by a Nationally Recognized Testing Laboratory (NRTL) No

Features

Locking Miter Bar
Built In Dust Port
Non Slip Rubber Feet
Compact and Completely Portable