

MACHINE SPECIFICATIONS



© Woodstock International, Inc. • Phone #: (800) 840-8420 • Web: www.woodstockint.com

MODEL W1824 2 HP 10" HYBRID CABINET TABLE SAW WITH EXTENSION TABLE

Product Dimensions

Weight..... 404 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 58 x 36 x 40 in.
Footprint (Length x Width)..... 20 x 21-1/2 in.

Shipping Dimensions

Carton #1

Type..... Cardboard Box on Wood Skids
Content..... Machine
Weight..... 380 lbs.
Length x Width x Height..... 26 x 30 x 43 in.

Carton #2

Type..... Cardboard Box
Content..... Fence
Weight..... 18 lbs.
Length x Width x Height..... 37 x 15 x 6 in.

Carton #3

Type..... Cardboard Box
Content..... Rails
Weight..... 32 lbs.
Length x Width x Height..... 60 x 5 x 4 in.

Electrical

Power Requirement..... 110V or 220V, Single-Phase, 60 Hz
Prewired Voltage..... 220V
Full-Load Current Rating..... 16A at 110V, 8A at 220V
Minimum Circuit Size..... 20A at 110V, 15A at 220V
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 6 ft.
Power Cord Gauge..... 14 AWG
Plug Included..... Yes
Included Plug Type..... 6-20 for 220V
Recommended Plug Type..... 5-20 for 110V
Switch Type..... ON/OFF Push Button Switch w/Large Shut-Off Paddle
Voltage Conversion Kit..... X1824204-1 for 110V

Motors

Main

Horsepower.....	2 HP
Phase.....	Single-Phase
Amps.....	16A/8A
Speed.....	3450 RPM
Type.....	TEFC Capacitor-Start Induction
Power Transfer	Poly-V Belt Drive
Bearings.....	Sealed & Permanently Lubricated

Main Specifications

Main Information

Table Saw Type.....	Hybrid
Maximum Blade Diameter.....	10 in.
Arbor Size.....	5/8 in.
Arbor Speed.....	3850 RPM
Maximum Width of Dado.....	13/16 in.
Blade Tilt Direction.....	Left
Max Blade Tilt.....	45 deg.
Maximum Depth of Cut At 90 Degrees.....	3-1/8 in.
Maximum Depth of Cut At 45 Degrees.....	2-3/16 in.
Max Rip Right of Blade w/Included Fence & Rails.....	30 in.
Max Rip Left of Blade w/Included Fence & Rails.....	12 in.

Additional Blade Information

Included Blade Information.....	10" x 40T
Riving Knife/Spreader Thickness.....	0.100 in.
Required Blade Body Thickness.....	0.071 - 0.094 in.
Required Blade Kerf Thickness.....	0.102 - 0.126 in.
Rim Speed at Max Blade Diameter.....	10,100 FPM

Table Information

Floor to Table Height.....	34 in.
Table Size with Extension Wings Width.....	55 in.
Table Size with Extension Wings Depth.....	27 in.
Distance Front of Table to Center of Blade.....	16 in.
Distance Front of Table to Blade At Maximum Cut.....	11-1/2 in.
Main Table Size Thickness.....	1-1/2 in.

Fence Information

Fence Type.....	Camlock T-Shape w/ Wraparound Rail-Mounting & HDPE Face
Fence Size Length.....	34-1/4 in.
Fence Size Width.....	3-1/8 in.
Fence Size Height.....	2-1/2 in.
Fence Rail Type.....	Square Steel Tubing
Fence Rail Length.....	59-5/8 in.
Fence Rail Width.....	2 in.
Fence Rail Height.....	1-5/8 in.

Miter Gauge Information

Miter Gauge Slot Type.....	T-Slot
Miter Gauge Slot Size Width.....	3/4 in.
Miter Gauge Slot Size Height.....	3/8 in.

Construction

Table.....	Precision-Ground Cast Iron
Wings.....	Cast Iron; Phenolic w/Low Friction Surface
Cabinet.....	Pre-Formed Steel
Trunnions.....	Cast Iron
Fence Assembly.....	Steel with HDPE Side Plates
Rails.....	Steel
Miter Gauge Construction.....	Aluminum
Guard.....	Steel and Clear Plastic
Body/Cabinet Paint Type/Finish.....	Powder Coated
Arbor Bearings.....	Sealed & Permanently Lubricated

Other Related Information

Number of Dust Ports.....	1
Dust Port Size.....	4 in.
Compatible Mobile Base.....	D2057A

Other

Country of Origin	China
Warranty	2 Years
Approximate Assembly & Setup Time	1 Hour
Serial Number Location	ID Label on Cabinet
ISO 9001 Factory	Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL)	Yes

Features

Precision-Ground Cast-Iron Table
Cast-Iron Trunnions
4" dust port
T-slot miter gauge
Camlock T-shaped fence with HDPE face
Easy glide fence system
Powder coated paint
Quick-release riving knife and blade guard assembly
Knurled knobs for adjusting fence
Includes regular & dado blade table inserts
Device on blade guard allows enabling/disabling anti-kickback pawls