

MACHINE SPECIFICATIONS

© Grizzly Industrial, Inc. • Phone #: (360) 647-0802 • Web: www.shopfoxtools.com



MODEL W1825 19" 3 HP HEAVY DUTY BANDSAW

Product Dimensions

Weight..... 427 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 36 x 32 x 76 in.
Footprint (Length x Width)..... 29-1/2 x 17-3/4 in.

Shipping Dimensions

Type..... Wood Crate
Content..... Machine
Weight..... 502 lbs.
Length x Width x Height..... 22 x 33 x 84 in.
Must Ship Upright..... Yes

Electrical

Power Requirement..... 220V, Single-Phase, 60 Hz
Prewired Voltage..... 220V
Full-Load Current Rating..... 12A
Minimum Circuit Size..... 15A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 6 ft.
Plug Included..... Yes
Included Plug Type..... 6-15
Switch Type..... Magnetic Switch w/Overload Protection

Motors

Main

Horsepower..... 3 HP
Phase..... Single-Phase
Amps..... 12A
Speed..... 1725 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer Belt Drive
Bearings..... Shielded & Permanently Lubricated
Centrifugal Switch/Contacts Type..... External

Main Specifications

Main Specifications

Bandsaw Size..... 19 in.
Max Cutting Width (Left of Blade)..... 18-1/4 in.
Max Cutting Width (Left of Blade) w/Fence..... 16-7/8 in.
Max Cutting Height (Resaw Height)..... 12 in.
Blade Speeds..... 1700, 3500 FPM

Blade Information

Standard Blade Length.....	143 in.
Blade Length Range.....	141-1/2 - 143 in.
Blade Width Range.....	1/8 - 1-1/4 in.
Type of Blade Guides.....	Ball Bearing
Guide Post Adjustment Type.....	Rack & Pinion
Has Quick-Release.....	Yes

Table Information

Table Length.....	26-3/4 in.
Table Width.....	19 in.
Table Thickness.....	1-1/2 in.
Table Tilt.....	Left 5, Right 45 deg.
Table Tilt Adjustment Type.....	Rack & Pinion
Floor-to-Table Height.....	37-1/2 in.
Fence Locking Position.....	Front
Fence is Adjustable for Blade Lead.....	Yes
Resaw Fence Attachment Included.....	Yes
Miter Gauge Included.....	Yes

Construction Materials

Table.....	Precision Ground Cast Iron
Trunnion.....	Cast Iron
Fence.....	Cast Iron Fence with Extruded Aluminum Resaw Fence
Base/Stand.....	Pre-Formed Steel
Frame/Body.....	Pre-Formed Steel
Wheels.....	Computer-Balanced Cast Iron
Tire.....	Polyurethane
Wheel Cover	Pre-Formed Steel
Paint Type/Finish.....	Powder Coated

Other Related Information

Wheel Diameter.....	18-7/8 in.
Wheel Width.....	1-1/4 in.
Number of Dust Ports.....	2
Dust Port Size.....	4 in.
Compatible Mobile Base.....	D2058A

Other

Country of Origin	Taiwan
Warranty	2 Years
Approximate Assembly & Setup Time	1 Hour
Serial Number Location	ID Label on Upper Wheel Cover
ISO 9001 Factory	Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL)	Yes

Features

- Cast-Iron Table Trunnion
- Ball Bearing Blade Guides
- Micro-Adjusting Rack & Pinion Table Tilt
- Blade Tension Indicator
- Magnifying Window over Fence Scale
- Height Scale for Upper Blade Guides
- Blade Tracking Window
- Hinged Wheel Covers with Safety Lock
- Included Miter Gauge
- Included 3/4" Blade
- Two 4" Dust Ports
- Deluxe Cast-Iron Fence with Extruded Aluminum Resaw Fence Attachment
- Foot Brake Stop
- Rack and Pinion Upper Blade Guide Height Adjustment
- Quick-Change Blade Release/Tensioner
- Computer-Balanced Cast-Iron Wheels